- 1 WHAT IS CLAIMED IS:
- 2 1. An automobile transmission for transmitting driving
- 3 force of an engine to wheels while changing a rotation speed of
- 4 a crankshaft of said engine, comprising:
- a main shaft connected with said crankshaft through
- 6 a clutch and having a plurality of first drive gears;
- 7 a counter shaft provided below and in parallel with
- 8 said main shaft and having first driven gears meshing with said
- 9 first drive gears and having a second drive gear;
- a drive/shaft provided below and in parallel with said
- 11 counter shaft and having a second driven gear meshing with said
- 12 second drive gear;
- 13 a front differential provided at a front end of said
- 14 drive shaft:
- / a transmission case for accommodating said main shaft,
- 16 said counter shaft, said drive shaft and said front differential;
- 17 and
- 18 / a space formed in a front part of said transmission
- 19 case.
- 20
- 21 2. The transmission according to claim 1, further
- 22 comprising:
- a center differential provided at a rear end of said
- 24 counter shaft for distributing a driving force into one for front
- 25 wheels and one for rear wheels; and

1	an extension case connected with a rear end of said
2	transmission case for accommodating said center differential.
3	
4	3. The transmission according to claim 2, further
5	comprising;
6	a sub transmission accommodated in said space for
7 -	transmitting driving force of said engine to said main shaft
8	through said counter shaft while reducing said rotation speed
9	of said engine.
10	
11	4. The transmission according to claim 1, wherein
12	said transmission case comprises a plurality of
13	dividable members each of which has a cylindrical configuration
14	longitudinally extending.
15	
16	5. The transmission according to claim 1, wherein
17	said counter shaft is offset in one widthwise direction
18	with respect to said main shaft and said drive shaft is offset
19	in the other widthwise direction with respect to said main shaft.
20	
21	6. The transmission according to claim 3, wherein
22	said sub transmission includes reduction gears mounted

\$\dip

23

on said main shaft and said counter shafts.